4L60-E RANGE REFERENCE CHART

Shift solenoid states and holding / apply device operation

RANGE	GEAR	SHIFT SOLENOIDS		1 2-4 BAND	2 REVERSE INPUT CLUTCH	3 OVERRUN CLUTCH	4 FORWARD CLUTCH	5 FORWARD SPRAG ASSEMBLY	6 3-4 CLUTCH	7 LOW ROLLER CLUTCH	8 LOW/REV. CLUTCH
		1-2	2-3								
PARK		ON*	ON*								APPLIED
REVERSE		ON*	ON*		APPLIED						APPLIED
NEUTRAL		ON*	ON*								
D	1st	ON	ON				APPLIED	HOLDING		HOLDING	
	2nd	OFF	ON	APPLIED			APPLIED	HOLDING			
	3rd	OFF	OFF				APPLIED	HOLDING	APPLIED		
	4th	ON	OFF	APPLIED			APPLIED		APPLIED		
3	1st	ON	ON				APPLIED	HOLDING		HOLDING	
	2nd	OFF	ON	APPLIED			APPLIED	HOLDING			
	3rd	OFF	OFF			APPLIED	APPLIED	HOLDING	APPLIED		
2***	1st**	ON	ON			APPLIED	APPLIED	HOLDING		HOLDING	
	2nd	OFF	ON	APPLIED		APPLIED	APPLIED	HOLDING			
1***	1st	ON	ON			APPLIED	APPLIED	HOLDING		HOLDING	APPLIED
	2nd	OFF	ON	APPLIED		APPLIED	APPLIED	HOLDING			

APPLIED **HOLDING** D = overdrive range | Blank cells match the supplied chart.

Source notation retained: *, **, and ***. Their footnote definitions were not visible in the supplied image.